

primus®

GET AHEAD IN LAUNDRY+



DX13/13

STACKED TUMBLE DRYER



SAFETECH FIRE SUPPRESSION SYSTEM
For maximal safety of your operations



SENSO DRY+ TECHNOLOGY
Lower energy and utility costs, lower linen replacement costs



CLOUD - BASED PLATFORM
to easily monitor your laundry everywhere and at any time



RADIAL AND AXIAL AIRFLOW
For maximal heat transfer, low energy consumption and short drying time



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a 3 - year warranty

FEATURES & BENEFITS

Features

- Standard galvanized drum
- Stainless steel front panel with black painted door
- Large door opening for easy loading & unloading
- Self cleaning lint screen

Options

- Coin operated
- Stainless steel drum
- Reversing drum

Control

- XControl FLEX PLUS – fully programmable and customizable cycles 7" touch screen.
 - User - friendly screen with operating instructions built in as part of the control
 - Complete control content available in 34 languages
- Easy - To - Use Microprocessor - Dual Digital Control or OPL Micro
- Coin Operated Easy - To - Use Microprocessor - XQ - Control (ECT)

SPECIFICATIONS

TYPE		PTT30EVHJRJS6N0000
CAPACITY		
Capacity 1:18	kg (lb)	2 x 17(38)
Capacity 1:22	kg (lb)	2 x 14(31)
Drum volume	l	2 x 300
Drum diameter	mm	Ø 762
AIRFLOW	l/sec	310 - 380
MOTORS		
Fan	kW	0,40
Drive	kW	0,40
NOISE LEVEL	dBA	63
GAS HEATING		
Gas connection	NPT	1/2"
Electrical connection		
Energy per pocket	kW	16.1 - 77
	kBTU/h	55 - 73
ELECTRICAL HEATING		
Electrical Specs - amps	Electric J	400-415V/50-60Hz/3Ph
		30*2
Energy per pocket	kW	12 - 21
EXHAUST	mm	150 - 200
DIMENSIONS		
H×W×D	mm	1940x800x1100
Net weight	kg	265 - 275
TRANSPORT DATA		
Packed H×W×D	mm	2030x830x1190
Gross weight	kg	280 - 290

DIMENSIONS

	A	B	C	D	E	F	G	H	I	J	K
DX13/13	710	1245	1225	290	270	635	730	1100	695	800	1940
								depth		width	height

