

primus®

GET AHEAD IN LAUNDRY



DX20/20

## STACKED TUMBLE DRYER



**SAFETECH FIRE SUPPRESSION SYSTEM**  
For maximal safety of your operations



**SENSO DRY+ TECHNOLOGY**  
Lower energy and utility costs, lower linen replacement costs



**CLOUD - BASED PLATFORM**  
to easily monitor your laundry everywhere and at any time



**RADIAL AND AXIAL AIRFLOW**  
For maximal heat transfer, low energy consumption and short drying time



**EXTRA LARGE DOOR OPENING**  
For easy loading and unloading



**IMPROVED DURABILITY**  
for your peace of mind with a 3 - year warranty

### FEATURES & BENEFITS

#### Features

- Standard galvanized drum
- Stainless steel front panel with black painted door
- Large door opening for easy loading & unloading
- Self cleaning lint screen

#### Options

- Coin operated
- Stainless steel drum
- Reversing drum

#### Control

- XControl FLEX PLUS – fully programmable and customizable cycles 7" touch screen.
  - User - friendly screen with operating instructions built in as part of the control
  - Complete control content available in 34 languages
- Easy - To - Use Microprocessor - Dual Digital Control or OPL Micro
- Coin Operated Easy - To - Use Microprocessor - XQ - Control (ECT)

## SPECIFICATIONS

TYPE		PTT45LVHJRXS6N0000	
CAPACITY			
Capacity 1:18	kg (lb)	2 x 24(51)	
Capacity 1:22	kg (lb)	2 x 20(42)	
Drum volume	l	2 x 420	
Drum diameter	mm	Ø 838	
AIRFLOW	l/sec	570	
MOTORS			
Fan	kW	0,40	
Drive	kW	0,40	
NOISE LEVEL	dBA	65	
GAS HEATING			
Gas connection	NPT	1/2"	
Electrical connection			
Energy per pocket	kW	23.4 - 100.2	
	kBTU/h	80 - 95	
ELECTRICAL HEATING			
Electrical Specs - amps	Gas X	200-240V/50-60Hz/3Ph	6*2
Energy per pocket	kW	-	
EXHAUST	mm	250	
DIMENSIONS			
H×W×D	mm	2065x875x1260	
Net weight	kg	315	
TRANSPORT DATA			
Packed H×W×D	mm	2160x900x1370	
Gross weight	kg	335	

## DIMENSIONS

	A	B	C	D	E	F	G	H	I	J	K
DX20/20	810	1280	1250	260	235	735	830	1260	770	875	2065
								depth		width	height

