



DX24 TUMBLE DRYER



SAFETECH FIRE SUPPRESSION SYSTEM
For maximal safety of your operations



SENSO DRY+ TECHNOLOGY
Lower energy and utility costs, lower linen replacement costs



CLOUD - BASED PLATFORM
to easily monitor your laundry everywhere and at any time



RADIAL AND AXIAL AIRFLOW
For maximal heat transfer, low energy consumption and short drying time



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a 3 - year warranty

FEATURES & BENEFITS

Features	Options	Control
<ul style="list-style-type: none"> Standard galvanized drum Stainless steel front panel with black painted door Large door opening for easy loading & unloading Self cleaning lint screen AutoDry capability for OPL 	<ul style="list-style-type: none"> Coin operated Stainless steel drum Reversing drum 	<ul style="list-style-type: none"> XControl FLEX PLUS – fully programmable and customizable cycles 7" touch screen. <ul style="list-style-type: none"> User - friendly screen with operating instructions built in as part of the control Complete control content available in 34 languages Easy - To - Use Microprocessor - Dual Digital Control or OPL Micro Coin Operated Easy - To - Use Microprocessor - XQ - Control (ECT)

SPECIFICATIONS

TYPE		PT055LVH-JRXS6N000
CAPACITY		
Capacity 1:18	kg (lb)	27(59)
Capacity 1:22	kg (lb)	24(55)
Drum volume	l	490
Drum diameter	mm	Ø 838
AIRFLOW	l/sec	330
MOTORS		
Fan	kW	0,40
Drive	kW	0,40
NOISE LEVEL	dba	61
GAS HEATING		
Gas connection	NPT	1/2"
Electrical connection		
Energy	kW	30.8 - 32.8
	kBTU/h	105 - 112
STEAM HEATING		
Steam connection	NPT	3/4"
Electrical Specs - amps	Gas X 200-240V/50-60Hz/3Ph	7
Steam pressure	bar	5.5 - 8.6
ELECTRICAL HEATING		
Electrical connection		
Energy	kW	18 - 27
EXHAUST	mm	200
DIMENSIONS		
H×W×D	mm	1700x870x1350
Net weight	kg	195 - 210
TRANSPORT DATA		
Packed H×W×D	mm	1790x900x1450
Gross weight	kg	210 - 215

DIMENSIONS

	A	B	C	D	E	F	G*	H*	I*	J	K
DX24	810	A670	A850	A935	A1350	A1700	A395	A510	A40	A775	A875

depth height

width

*Fire suppression system optional - may not be on machine.

