



# **DX34** TUMBLE DRYER



SAFETECH FIRE SUPPRESSION SYSTEM For maximal safety of your operations



RADIAL AND AXIAL AIRFLOW For maximal heat transfer, low energy consumption and short drying time



SENSO DRY+ TECHNOLOGY Lower energy and utility costs, lower linen replacement costs



**CLOUD - BASED PLATFORM** to easily monitor your laundry everywhere and at any time





EXTRA LARGE DOOR OPENING For easy loading and unloading



IMPROVED DURABILITY for your peace of mind with a 3 year warranty

# FEATURES & BENEFITS

### Features

- Standard galvanized drum •
- Stainless steel front panel with black • painted door
- Large door opening for easy loading & unloading
- Self cleaning lint screen •
- ${\sf AutoDry\ capability\ for\ OPL}$ •

#### Options

- Coin operated
- Stainless steel drum
- Reversing drum

#### Control

- XControl FLEX PLUS fully programmable and customizable cycles 7" touch screen.
  - User friendly screen with operating instructions built in as part of the control
  - Complete control content available in 34 languages
- Easy To Use Microprocessor Dual Digital Control or OPL Micro
- Coin Operated Easy To Use • Microprocessor - XQ - Control (ECT)


# SPECIFICATIONS

| SPECIFICATIONS                   |                      |                   |  |  |  |  |  |
|----------------------------------|----------------------|-------------------|--|--|--|--|--|
| ТҮРЕ                             |                      | PT075LVHJRXS6N000 |  |  |  |  |  |
| CAPACITY                         |                      |                   |  |  |  |  |  |
| Capacity 1:18                    | kg (lb)              | 35(77)            |  |  |  |  |  |
| Capacity 1:22                    | kg (lb)              | 34(75)            |  |  |  |  |  |
| Drum volume                      |                      | 634               |  |  |  |  |  |
| Drum diameter                    | mm                   | Ø 940             |  |  |  |  |  |
| AIRFLOW                          | l/sec                | 380               |  |  |  |  |  |
| MOTORS                           |                      |                   |  |  |  |  |  |
| Fan                              | kW                   | 0,40              |  |  |  |  |  |
| Drive                            | kW                   | 0,40              |  |  |  |  |  |
| NOISE LEVEL                      | dBA                  | 60                |  |  |  |  |  |
| GAS HEATING                      |                      |                   |  |  |  |  |  |
| Gas connection                   | NPT                  | 1/2"              |  |  |  |  |  |
| Electrical connection            |                      |                   |  |  |  |  |  |
| Energy                           | kW                   | 35.8 - 48.4       |  |  |  |  |  |
|                                  | kBTU/h               | 150               |  |  |  |  |  |
| STEAM HEATING                    |                      |                   |  |  |  |  |  |
| Steam connection                 | NPT                  | 3/4"              |  |  |  |  |  |
| Electrical Specs Gas<br>- amps X | 200-240V/50-60Hz/3Ph | 7                 |  |  |  |  |  |
| Steam pressure                   | bar                  | 5.3 - 6.9         |  |  |  |  |  |
| ELECTRICAL HEATING               |                      |                   |  |  |  |  |  |
| Electrical connection            |                      |                   |  |  |  |  |  |
| Energy                           | kW                   | 21 - 36           |  |  |  |  |  |
| EXHAUST                          | mm                   | 200 - 250         |  |  |  |  |  |
| DIMENSIONS                       |                      |                   |  |  |  |  |  |
| H×W×D                            | mm                   | 1960x980x1190     |  |  |  |  |  |
| Net weight                       | kg                   | 325 - 335         |  |  |  |  |  |
| TRANSPORT DATA                   |                      |                   |  |  |  |  |  |
| Packed H×W×D                     | mm                   | 2120x1050x1420    |  |  |  |  |  |
| TACKEUTI                         |                      |                   |  |  |  |  |  |

## DIMENSIONS

|      | А   | В   | С     | D      | <b>E</b> * | F     | G   | Η*  | 1*  | J*  | К   | L    |
|------|-----|-----|-------|--------|------------|-------|-----|-----|-----|-----|-----|------|
| DX34 | 740 | 860 | 1190  | 1960   | 465        | 980   | 840 | 190 | 150 | 350 | 900 | 1000 |
|      |     |     | depth | height |            | width |     |     |     |     |     |      |

\*Fire suppression system optional - may not be on machine.



Right side

Rear side