

primus®

GET AHEAD IN LAUNDRY



PC60

HARDMOUNT WASHER-EXTRACTORS



PATENTED WATER GUARDIAN
Detects leaking valves



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a
3-year warranty


FEATURES & BENEFITS

FEATURES

- Rigid mounted, normal spin, 200G factor
- Stainless Steel drum and tub
- High capacity water inlets
- Large drain valve
- Large door opening for easy loading and unloading
- Industry-leading flexible water level settings
- patented Fill and Drain leak detection saves water
- Lighter, consumption-optimized frame
- Designed to reduce sound and vibration levels

PLATFORM: XCONTROL FLEX

- Available with XControl FLEX for Vend
- Full color, touch screen display
- Clear step-by-step instructions available in 34 languages
- Machine programming & performance data accessible through cloud. Remotely access to live machine data on mobile device
- VEND:
 - » 15 easy-to-use washer cycle modifier
- Count up timer
- Over-the-air updates



Consult your sales representative for availability

Primus by Alliance Laundry Systems


Specifications

Model	PCT060VHJVXB60J000
Control Option	XControl FLEX
Capacity - [kg (lb)]	27.2 (60)
Overall Width - [mm (in)]	865 (34.1)
Overall Depth - [mm (in)]	1135 (44.7)
Overall Height - [mm (in)]	1267 (49.9)
Cylinder Diameter - [mm (in)]	762 (30)
Cylinder Depth - [mm (in)]	559 (22)
Cylinder Volume - [l (cu. ft.)]	255 (9.0)
Door Opening Size - [mm (in)]	414 (16.3)
Door Bottom to Floor - [mm (in)]	379 (14.9)
Water Inlet Connection - [mm(in)]	4 @ 19 (0,75)
Drain Diameter - [mm (in)]	1 @ 76 (3)
Drain Height to Floor - [mm (in)]	124 (4,9)
Total #of Speeds	9
CYLINDER SPEEDS - [RPM(G-FORCE)] Ultra High	686(200)
VOLTAGEWIRES/ CIRCUIT BREAKER -	
FLA120/60/1	N/A
200-240V/50-60Hz/3-1Ph	15 - 4 (1 Ph) 15 - 3 (3 Ph)
SHIPPING DIMENSIONS	
AP-PROX. - [mm (in)]	
Width	953 (37.5)
Depth	1191 (46.9)
Height	1430 (56.3)
Motor Power Consumption - [kW (HP)]	2.2 (3)
Net Weight - [kg (lb)]	308 (680)
Shipping Weight - [kg (lb)]	327 (720)
Slat Crate Shipping Weight - [kg (lb)]	381 (840)
Agency Approvals	CSA/UL/IEC/KTL

Hardmount Washer-Extractor

	Height	Width	Depth
PC60	1267	865	1135

All measurements in mm.



Primus preserves the right to change the machines and the specification in this leaflet at any time, without prior notice. Details and photographs are only for information and never binding. www.primuslaundry.com