

primus®

GET AHEAD IN LAUNDRY



PSG30

Stacked Washer-Extractor/ Tumble Dryer



SAFETECH FIRE SUPPRESSION SYSTEM
For maximal safety of your operations



SENSO DRY+ TECHNOLOGY
Lower energy and utility costs,
lower linen replacement costs



CLOUD - BASED PLATFORM
to easily monitor your laundry
everywhere and at any time



RADIAL AND AXIAL AIRFLOW
For maximal heat transfer, low
energy consumption and short
drying time



EXTRA LARGE DOOR OPENING
For easy loading and unloading



IMPROVED DURABILITY
for your peace of mind with a 3 -
year warranty

FEATURES & BENEFITS

Features

- Ideal for limited space settings
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

Maximize Time and Space

PRIMUS stacked washer-extractor/
tumble dryer is a unique product that
truly delivers increased productivity.
Featuring the Xtronic Touch Control.



PLATFORM: XCONTROL FLEX

- Available with XControl FLEX
- 7" (5" on stack tumbler dryers), full color, touch screen display
- Clear step-by-step instructions available in 34 languages
- Machine programming & performance data accessible through cloud. Remotely access to live machine data on mobile device
- VEND:
 - » 5 standard dry programmes (High, Medium, Low, Delicate, No Heat)
 - » 15 easy-to-use washer cycle modifier
- Count up timer
- Over-the-air updates

Stacked Washer-Extractor/Tumble Dryer

Specifications

| | | | PSG030LVEJXS3YL000 | |
|--|--------------|-------------------------|---------------------|----------------------|
| | | | Washer-Extractor | Tumble Dryer |
| Control Option | | | XControl FLEX | |
| Capacity - lb (kg) | | | 30 (13.6) x 2 | |
| Overall Width - in (mm) | | | 31.4 (797) | |
| Overall Depth - in (mm) | | | 45.5 (1152) | |
| Overall Height - in (mm) | | | 79.7 (2023) | |
| Cylinder Diameter - in (mm) | | | 24.0 (610) | 30.0 (762) |
| Cylinder Depth - in (mm) | | | 16.0 (406) | 26.0 (660) |
| Cylinder Volume - cu. ft (liters) | | | 4.2 (119) | 10.6 (300) |
| Reversing Cylinder | | | - | Standard |
| Door Opening Size - in (mm) | | | 14.3 (363) | 22.6 (574) |
| Door Bottom to Floor - in (mm) | | | 14.0 (356) | 51.3 (1303) |
| Water Inlet Connection - in (mm) | | | 2 x 0.75 (19) | - |
| Drain Diameter - in (mm) | | | 1 x 3 (76) | - |
| Drain Height to Floor - in (mm) | | | 4.3 (108) | - |
| Heat Input Power - Btu/hr (kW, Mj/hr.) | | | - | 73,000 (21.4, 77.0) |
| Gas Connection - in | | | - | 1/2 NPT |
| Air Outlet - in (mm) | | | - | 8.0 (200) Elliptical |
| Airflow - cfm (l/sec) | | | - | 400 (190) |
| Motor - HP (kW) | Fan | | - | 0.5 (0.4) |
| | Drive | | 1 (0.75) | 0.3 (0.2) |
| Total # of Speeds | | | 9 | - |
| Cylinder Speeds - RPM (G-Force) | Gentle | | 34 (0.4) | - |
| | Wash | | 48 (0.8) | - |
| | Distribution | | 86 (2.5) | - |
| | Very Low | | 282 (27) | - |
| | Low | | 485 (80) | - |
| | Medium | | 542 (100) | - |
| | High | | 606 (125) | - |
| | Very High | | 664 (150) | - |
| | Ultra High | | 766 (200) | - |
| Electrical Specs - amps | Gas X | 200-240V/50 60ĥ / 1 3/p | 15 | 10 |
| Shipping Dimensions Approx. - in (mm) | Width | | 34.5 (876) | |
| | Depth | | 47.0 (1194) | |
| | Height | | 83.0 (2108) | |
| Net Weight - lb (kg) | | | 770 (349) | |
| Shipping Weight - lb (kg) | | | 787 (357) | |
| Agency Approvals | | | CSA/UL/AGA/KTL/TISI | |