

primus®

GET AHEAD IN LAUNDRY



PSG50

## Stacked Washer-Extractor/ Tumble Dryer



**SAFETECH FIRE SUPPRESSION SYSTEM**  
For maximal safety of your operations



**SENSO DRY+ TECHNOLOGY**  
Lower energy and utility costs,  
lower linen replacement costs



**CLOUD - BASED PLATFORM**  
to easily monitor your laundry  
everywhere and at any time



**RADIAL AND AXIAL AIRFLOW**  
For maximal heat transfer, low  
energy consumption and short  
drying time



**EXTRA LARGE DOOR OPENING**  
For easy loading and unloading



**IMPROVED DURABILITY**  
for your peace of mind with a 3 -  
year warranty

### FEATURES & BENEFITS

#### Features

- Ideal for limited space settings
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

#### Maximize Time and Space

PRIMUS stacked washer-extractor/  
tumble dryer is a unique product that  
truly delivers increased productivity.  
Featuring the Xtronic Touch Control.



#### PLATFORM: XCONTROL FLEX

- Available with XControl FLEX
- 7" (5" on stack tumbler dryers), full color, touch screen display
- Clear step-by-step instructions available in 34 languages
- Machine programming & performance data accessible through cloud. Remotely access to live machine data on mobile device
- VEND:
  - » 5 standard dry programmes (High, Medium, Low, Delicate, No Heat)
  - » 15 easy-to-use washer cycle modifier
- Count up timer
- Over-the-air updates

# Stacked Washer-Extractor/Tumble Dryer

## Specifications

			PSG050LVEJXS3YL000	
			Washer-Extractor	Tumble Dryer
Control Option			XControl FLEX	
Capacity - lb (kg)			50 (23) x 2	
Overall Width - in (mm)			34.4 (875)	
Overall Depth - in (mm)			51.3 (1302)	
Overall Height - in (mm)			84.3 (2141)	
Cylinder Diameter - in (mm)			26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)			20.3 (515)	30.0 (762)
Cylinder Volume - cu. ft (liters)			6.3 (178)	14.8 (419)
Reversing Cylinder			-	Standard
Door Opening Size - in (mm)			16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)			14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)			2 x 0.75 (19)	-
Drain Diameter - in (mm)			1 x 3 (76)	-
Drain Height to Floor - in (mm)			4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mj/hr.)			-	95,000 (27.8, 100)
Gas Connection - in			-	1/2 NPT
Air Outlet - in (mm)			-	10.0 (250) Elliptical
Airflow - cfm (l/sec)			-	600 (285)
Motor - HP (kW)	Fan		-	0.5 (0.4)
	Drive		2 (1.5)	0.5 (0.4)
Total # of Speeds			9	-
Cylinder Speeds - RPM (G-Force)	Gentle		33 (0.4)	-
	Wash		46 (0.8)	-
	Distribution		82 (2.5)	-
	Very Low		269 (27)	-
	Low		464 (80)	-
	Medium		518 (100)	-
	High		579 (125)	-
	Very High		635 (150)	-
	Ultra High		733 (200)	-
Electrical Specs - amps	Gas X	200-240V/50 60z   /1 3/p	15	10
Shipping Dimensions Approx. - in (mm)	Width		35.5 (902)	
	Depth		54.0 (1372)	
	Height		89.0 (2261)	
Net Weight - lb (kg)			910 (413)	
Shipping Weight - lb (kg)			930 (422)	
Agency Approvals			CSA/UL/AGA/KTL/TISI	